

Size	Model	STATOR															ROTOR							
		CONFIGURATION					FIT @ 75° F (Inch)										Minor Diameter Tolerance +/-	CONFIGURATION						
		Tube OD/ID Inch	Length Inch	Cutback Inch	Lobes	Stages	NBR-HPW					NBR - HPO						Overall Length Inch	Contour Length Inch	Ecc Inch	Major Diameter Inch	Head Diameter Inch	Thread Connection	Weight lb
4 3/4"	AT475456.0	4.75/3.75	187.00	8.00/8.00	4/5	6.0	0.000	-	-0.018	-	-	0.000	-	-0.018	-	-	0.010	179.00	173.00	0.246	2.912	2.750	2.375 HEF Modified	244
	AT475456.3	4.75/3.75	207.00	8.00/8.00	4/5	6.3	0.000	-0.009	-0.018	-0.027	-	0.000	-0.009	-0.018	-0.027	-	0.010	188.00	182.00	0.246	2.912	2.750	2.375 HEF Modified	256
	AT475459.7	4.75/3.88	235.00	8.00/15.50	4/5	9.7	0.000	-0.010	-0.020	-0.030	-	0.000	-0.010	-0.020	-0.030	-	0.011	214.75	208.25	0.226	2.822	3.000	2.375 HEF Modified	278
	AT475568.3	4.75/3.75	242.50	8.00/8.00	5/6	8.3	0.014	0.004	-0.007	-0.022	-0.039	0.014	0.004	-0.007	-0.022	-0.039	0.010	229.50	223.00	0.207	2.916	3.125	2.375 HEF Modified	333
	AT475782.0	4.75/3.75	180.00	8.00/8.00	7/8	2.0	0.007	-	-0.010	-	-	0.007	-	-0.010	-	-	0.010	172.50	166.50	0.163	2.798	2.750	2.375 HEF Modified	239
	AT475782.2 SLOW	4.75/3.75	198.00	8.00/8.00	7/8	2.2	0.002	-0.008	-0.019	-0.029	-0.038	0.002	-0.008	-0.019	-0.029	-0.038	0.010	191.00	185.00	0.161	2.805	2.825	1.375-6 SA	270
	AT475782.6 ESX	4.75/3.75	229.25	8.00/8.00	7/8	2.6	-0.002	-0.014	-0.024	-0.034	-0.041	-0.002	-0.014	-0.024	-0.034	-0.041	0.010	220.00	214.25	0.174	3.095	2.750	2.375 HEF Modified	381
	AT475782.9	4.75/3.75	250.00	8.00/8.00	7/8	2.9	-0.002	-0.012	-0.022	-0.028	-	-0.002	-0.012	-0.022	-0.028	-	0.010	242.00	236.00	0.163	2.798	2.850	2.375 HEF	339
	AT475783.8	4.75/3.75	187.00	8.00/8.00	7/8	3.8	0.019	0.009	-0.001	-0.012	-0.032	0.019	0.009	-0.001	-0.012	-0.032	0.010	178.00	172.25	0.163	2.945	2.750	2.375 HEF Modified	283
	AT475784.5 SX	4.75/3.75	229.25	8.00/12.00	7/8	4.5	0.002	-	-0.018	-	-	0.002	-	-0.018	-	-	0.010	220.00	214.30	0.172	3.091	2.750	2.375 HEF Modified	381
	AT475785.0 RM	4.75/3.88	198.00	8.00/8.00	7/8	5.0	0.005	-0.005	-0.015	-0.025	-0.035	0.005	-0.005	-0.015	-0.025	-0.035	0.010	186.00	180.00	0.171	3.041	2.750	2.375 HEF Modified	311
	AT475785.0 WF	4.75/3.88	198.00	8.00/8.00	7/8	5.0	0.003	-0.007	-0.017	-0.027	-	0.003	-0.007	-0.017	-0.027	-	0.010	186.00	180.00	0.169	3.041	2.750	2.375 HEF Modified	316
AT475786.4	4.75/3.88	235.00	8.00/8.00	7/8	6.4	-	-0.005	-	-	-	-	-0.005	-	-	-	0.010	226.00	220.00	0.170	3.029	3.250	1.375-6 SA	372	
5"	AT500239.0	5.00/3.75	200.00	8.00/8.00	2/3	9.0	-	-	-0.057	-	-	-	-	-0.057	-	-	0.010	194.00	188.00	0.224	2.537	2.600	2.375 HEF Modified	183
	AT500456.0	5.00/3.75	187.00	8.00/8.00	4/5	6.0	0.000	-	-0.018	-	-	0.000	-	-0.018	-	-	0.010	179.00	173.00	0.246	2.912	2.750	2.375 HEF Modified	244
	AT500456.3	5.00/3.75	207.00	8.00/8.00	4/5	6.3	0.000	-0.009	-0.018	-0.027	-	0.000	-0.009	-0.018	-0.027	-	0.010	188.00	182.00	0.246	2.912	2.750	2.375 HEF Modified	256
	AT500459.7	5.00/3.88	235.00	8.00/15.50	4/5	9.7	0.000	-0.010	-0.020	-0.030	-	0.000	-0.010	-0.020	-0.030	-	0.011	214.75	208.25	0.226	2.822	3.000	2.375 HEF Modified	278
	AT500563.7 Hi Flow	5.00/4.00	250.00	8.00/15.50	5/6	3.7	0.015	-	-0.005	-	-	0.015	-	-0.005	-	-	0.010	229.75	223.25	0.235	3.120	3.250	1.375-6 SA	318
	AT500566.7	5.00/4.00	250.00	8.00/8.00	5/6	6.7	0.010	0.000	-0.010	-0.020	-	0.010	0.000	-0.010	-0.020	-	0.010	241.00	235.00	0.235	3.120	2.900	2.375 HEF Modified	383
	AT500568.3	5.00/3.75	242.50	8.00/8.00	5/6	8.3	0.014	0.004	-0.007	-0.022	-0.039	0.014	0.004	-0.007	-0.022	-0.039	0.010	229.50	223.00	0.207	2.916	3.125	2.375 HEF Modified	333
	AT5006710.0 (O)	5.00/4.00	275.00	8.00/16.00	6/7	10.0	-0.003	-0.014	-0.025	-0.034	-	-0.003	-0.014	-0.025	-0.034	-	0.010	266.00	260.00	0.192	3.256	3.400	2.875 HEF Modified	496
	AT500676.0	5.00/4.00	185.00	8.00/8.00	6/7	6.0	-0.009	-	-0.029	-	-0.054	-0.009	-	-0.029	-	-0.054	0.010	179.50	173.50	0.192	3.018	2.900	2.375 HEF Modified	282
	AT500678.0 (O)	5.00/4.00	250.00	8.00/8.00	6/7	8.0	-0.009	-0.019	-0.029	-0.039	-0.054	-0.009	-0.019	-0.029	-0.039	-0.054	0.010	241.00	235.00	0.192	3.018	2.900	2.375 HEF Modified	383
	AT500678.8 (O)	5.00/4.00	275.00	8.00/8.00	6/7	8.8	0.004	-0.008	-0.020	-0.027	-0.034	0.004	-0.008	-0.020	-0.027	-0.034	0.010	265.00	258.00	0.217	3.298	3.400	2.375 HEF Modified	496
	AT500679.0	5.00/4.00	250.00	8.00/8.00	6/7	9.0	0.000	-0.010	-0.020	-0.030	-0.040	0.000	-0.010	-0.020	-0.030	-0.040	0.010	241.00	235.00	0.194	3.190	3.250	2.375 API REG	378
	AT500782.0	5.00/3.75	180.00	8.00/8.00	7/8	2.0	0.007	-	-0.010	-	-	0.007	-	-0.010	-	-	0.010	172.50	166.50	0.163	2.798	2.750	2.375 HEF Modified	239
	AT500782.2 SLOW	5.00/3.75	198.00	8.00/8.00	7/8	2.2	0.002	-0.008	-0.019	-0.029	-0.038	0.002	-0.008	-0.019	-0.029	-0.038	0.010	191.00	185.00	0.161	2.805	2.825	1.375-6 SA	270
	AT500782.6 ESX	5.00/3.75	229.25	8.00/8.00	7/8	2.6	-0.002	-0.014	-0.024	-0.034	-0.041	-0.002	-0.014	-0.024	-0.034	-0.041	0.010	220.00	214.25	0.174	3.095	2.750	2.375 HEF Modified	381
	AT500782.9	5.00/3.75	250.00	8.00/8.00	7/8	2.9	-0.002	-0.012	-0.022	-0.028	-	-0.002	-0.012	-0.022	-0.028	-	0.010	242.00	236.00	0.163	2.798	2.850	2.375 HEF	339
	AT500783.0 ESX	5.00/4.00	250.00	16.00/8.00	7/8	3.0	-0.006	-0.016	-0.026	-	-	-0.006	-0.016	-0.026	-	-	0.010	233.50	227.00	0.180	3.258	3.400	1.375-6 SA	457
	AT500783.7	5.00/3.88	235.00	8.00/15.50	7/8	3.7	0.004	-0.006	-0.016	-0.025	-	0.004	-0.006	-0.016	-0.025	-	0.010	214.75	208.25	0.177	3.122	3.250	1.375-6 SA	377
	AT500783.8	5.00/3.75	187.00	8.00/8.00	7/8	3.8	0.019	0.009	-0.001	-0.012	-0.032	0.019	0.009	-0.001	-0.012	-0.032	0.010	178.00	172.25	0.163	2.945	2.750	2.375 HEF Modified	283
	AT500784.5 SX	5.00/3.75	229.25	8.00/12.00	7/8	4.5	0.002	-	-0.018	-	-	0.002	-	-0.018	-	-	0.010	220.00	214.30	0.172	3.091	2.750	2.375 HEF Modified	381
AT500785.0 RM	5.00/3.88	198.00	8.00/8.00	7/8	5.0	0.005	-0.005	-0.015	-0.025	-0.035	0.005	-0.005	-0.015	-0.025	-0.035	0.010	186.00	180.00	0.171	3.041	2.750	2.375 HEF Modified	311	

Size	Model	STATOR															ROTOR							
		CONFIGURATION					FIT @ 75° F (Inch)										Minor Diameter Tolerance +/-	CONFIGURATION						
		Tube OD/ID Inch	Length Inch	Cutback Inch	Lobes	Stages	NBR-HPW					NBR - HPO						Overall Length Inch	Contour Length Inch	Ecc Inch	Major Diameter Inch	Head Diameter Inch	Thread Connection	Weight lb
5"	AT500785.0 WF	5.00/3.88	198.00	8.00/8.00	7/8	5.0	0.003	-0.007	-0.017	-0.027	-	0.003	-0.007	-0.017	-0.027	-	0.010	186.00	180.00	0.169	3.041	2.750	2.375 HEF Modified	316
	AT500785.7	5.00/4.00	250.00	8.00/8.00	7/8	5.7	0.003	-0.007	-	-	-	0.003	-0.007	-	-	-	0.010	240.00	234.00	0.168	3.144	3.250	1.375-6 SA	416
	AT500786.4	5.00/3.88	235.00	8.00/8.00	7/8	6.4	-	-0.005	-	-	-	-	-0.005	-	-	-	0.010	226.00	220.00	0.170	3.029	3.250	1.375-6 SA	372
	AT500788.2	5.00/4.00	250.00	8.00/16.00	7/8	8.2	0.004	-	-0.016	-0.024	-0.038	0.004	-	-0.016	-0.024	-0.038	0.010	235.00	228.50	0.173	3.354	3.400	2.375 HEF Modified	488
	AT500896.0	5.00/4.00	250.00	8.00/8.00	8/9	6.0	-0.006	-0.015	-	-	-	-0.006	-0.015	-	-	-	0.010	241.00	235.00	0.163	3.198	3.380	1.375-6 SA	447
5.15"	AT5156710.9	5.15/4.00	275.00	12.00/12.00	6/7	10.9	0.001	-	-	-	-	0.001	-	-	-	-	0.010	269.00	258.00	0.215	3.419	3.500	1.375-6 SA	553
	AT515788.3 HT (O)	5.15/4.00	275.00	12.00/18.00	7/8	8.3	-0.001	-0.014	-0.024	-	-	-0.001	-0.014	-0.024	-	-	0.010	253.00	247.00		3.422	3.400	1.375-6 SA	513
5 1/4"	AT5256710.9	5.25/4.00	275.00	12.00/12.00	6/7	10.9	0.001	-	-	-	-	0.001	-	-	-	-	0.010	269.00	258.00	0.215	3.419	3.500	1.375-6 SA	553
	AT525788.3 HT (O)	5.25/4.00	275.00	12.00/18.00	7/8	8.3	-0.001	-0.014	-0.024	-	-	-0.001	-0.014	-0.024	-	-	0.010	253.00	247.00		3.422	3.400	1.375-6 SA	513
6 1/4"	AT625782.8	6.25/5.00	130.00	8.00/8.00	7/8	2.8	0.012	-	-	-	-	0.012	-	-	-	-	0.011	117.00	110.00	0.226	3.980	3.500	2.375 API REG	335
	AT625782.9 ESX	6.25/5.00	228.75	8.00/8.00	7/8	2.9	0.004	-0.009	-0.021	-	-	0.004	-0.009	-0.021	-	-	0.011	220.75	214.25	0.233	4.204	4.000	2.375 API REG	712
	AT625783.0 SLOW	6.25/5.00	204.00	8.00/8.00	7/8	3.0	0.004	-	-0.021	-	-	0.004	-	-0.021	-	-	0.011	190.00	183.50	0.230	4.120	4.000	2.375 API REG	547
	AT625783.3 ESX	6.25/5.00	260.00	8.00/8.00	7/8	3.3	0.004	-0.009	-0.021	-	-	0.004	-0.009	-0.021	-	-	0.011	252.00	245.50	0.233	4.204	4.000	2.375 API REG	812
	AT625784.8	6.25/5.00	203.25	8.00/8.00	7/8	4.8	0.012	-0.001	-0.017	-0.026	-	0.012	-0.001	-0.017	-0.026	-	0.011	194.25	187.75	0.226	3.980	3.500	2.375 API REG	554
6 1/2"	AT650457.0	6.50/5.50	210.00	7.50/7.50	4/5	7.0	0.011	0.001	-0.015	-0.030	-0.045	0.011	0.001	-0.015	-0.030	-0.045	0.015	202.50	195.50	0.355	4.220	4.000	2.875 API REG	576
	AT650565.4	6.50/5.31	212.00	8.00/8.00	5/6	5.4	0.004	-0.014	-0.021	-	-	0.004	-0.014	-0.021	-	-	0.010	203.00	196.00	0.297	4.158	4.000	2.875 API REG	601
	AT650568.2 (O)	6.50/5.50	246.00	11.00/11.00	5/6	8.2	0.018	0.005	-0.007	-0.020	-0.032	0.018	0.005	-0.007	-0.020	-0.032	0.010	233.00	226.00	0.335	4.371	4.500	2.875 SLIMLINE H-90	717
	AT650675.0	6.50/5.50	200.00	7.25/7.25	6/7	5.0	0.006	-0.009	-0.020	-0.031	-0.041	0.006	-0.009	-0.020	-0.031	-0.041	0.013	194.00	188.00	0.288	4.316	4.000	2.875 API REG	608
	AT650676.0	6.50/5.50	250.00	8.00/8.00	6/7	6.0	0.006	-0.009	-0.020	-0.031	-0.041	0.006	-0.009	-0.020	-0.031	-0.041	0.013	242.00	236.00	0.288	4.316	4.000	2.875 API REG	759
	AT650782.1 ESX	6.50/5.31	230.00	9.00/9.00	7/8	2.1	-0.007	-0.023	-0.033	-	-	-0.007	-0.023	-0.033	-	-	0.013	221.00	213.00	0.224	4.265	4.000	2.875 API REG	743
	AT650782.8	6.50/5.00	130.00	8.00/8.00	7/8	2.8	0.012	-	-	-	-	0.012	-	-	-	-	0.011	117.00	110.00	0.226	3.980	3.500	2.375 API REG	335
	AT650782.9 ESX	6.50/5.00	228.75	8.00/8.00	7/8	2.9	0.004	-0.009	-0.021	-	-	0.004	-0.009	-0.021	-	-	0.011	220.75	214.25	0.233	4.204	4.000	2.375 API REG	712
	AT650782.9 HTS	6.50/5.50	220.00	8.00/8.00	7/8	2.9	-0.002	-0.015	-0.025	-0.035	-	-0.002	-0.015	-0.025	-0.035	-	0.013	213.50	206.50	0.244	4.296	4.000	2.875 API REG	700
	AT650783.0	6.50/5.50	125.00	8.00/8.00	7/8	3.0	0.019	0.004	-0.008	-0.017	-	0.019	0.004	-0.008	-0.017	-	0.011	118.50	111.50	0.256	4.520	4.000	2.875 API REG	435
	AT650783.0 (6.25) SLOW	6.50/5.00	204.00	8.00/8.00	7/8	3.0	0.004	-	-0.021	-	-	0.004	-	-0.021	-	-	0.011	190.00	183.50	0.230	4.120	4.000	2.375 API REG	547
	AT650783.0 SLOW	6.50/5.50	204.00	7.50/7.50	7/8	3.0	0.006	-0.006	-0.014	-0.026	-	0.006	-0.006	-0.014	-0.026	-	0.011	197.50	191.00	0.255	4.570	4.000	2.875 API REG	754
	AT650783.3 ESX	6.50/5.00	260.00	8.00/8.00	7/8	3.3	0.004	-0.009	-0.021	-	-	0.004	-0.009	-0.021	-	-	0.011	252.00	245.50	0.233	4.204	4.000	2.375 API REG	812
	AT650783.3 HTS	6.50/5.50	245.00	8.00/8.00	7/8	3.3	0.000	-0.011	-0.021	-0.031	-	0.000	-0.011	-0.021	-0.031	-	0.012	238.50	231.50	0.255	4.500	4.000	2.875 API REG	877
	AT650784.8	6.50/5.00	203.50	8.00/8.00	7/8	4.8	0.012	-0.001	-0.017	-0.026	-	0.012	-0.001	-0.017	-0.026	-	0.011	194.25	187.75	0.226	3.980	3.500	2.375 API REG	554
	AT650785.0	6.50/5.50	194.50	8.00/8.00	7/8	5.0	0.019	0.004	-0.008	-0.017	-0.028	0.019	0.004	-0.008	-0.017	-0.028	0.011	188.00	181.00	0.256	4.520	4.000	2.875 API REG	694
	AT650786.0	6.50/5.50	235.00	8.00/8.00	7/8	6.0	0.019	0.004	-0.008	-0.017	-0.028	0.019	0.004	-0.008	-0.017	-0.028	0.011	223.00	216.00	0.256	4.520	4.500	2.875 API REG	831
	AT650786.4 (O)	6.50/5.50	245.00	8.00/8.00	7/8	6.4	0.019	0.004	-0.008	-0.017	-	0.019	0.004	-0.008	-0.017	-	0.011	238.50	231.50	0.256	4.520	4.000	2.875 API REG	883
6 3/4"	AT675457.0	6.75/5.50	210.00	7.50/7.50	4/5	7.0	0.011	0.001	-0.015	-0.030	-0.045	0.011	0.001	-0.015	-0.030	-0.045	0.015	202.50	195.50	0.355	4.220	4.000	2.875 API REG	576

Size	Model	STATOR															ROTOR							
		CONFIGURATION					FIT @ 75° F (Inch)										Minor Diameter Tolerance +/-	CONFIGURATION						
		Tube OD/ID Inch	Length Inch	Cutback Inch	Lobes	Stages	NBR-HPW					NBR - HPO						Overall Length Inch	Contour Length Inch	Ecc Inch	Major Diameter Inch	Head Diameter Inch	Thread Connection	Weight lb
6 3/4"	AT675565.4	6.75/5.31	212.00	8.00/8.00	5/6	5.4	0.004	-0.014	-0.021	-	-	0.004	-0.014	-0.021	-	-	0.010	203.00	196.00	0.297	4.158	4.000	2.875 API REG	601
	AT675568.2 (0)	6.75/5.50	246.00	11.00/11.00	5/6	8.2	0.018	0.005	-0.007	-0.020	-0.032	0.018	0.005	-0.007	-0.020	-0.032	0.010	233.00	226.00	0.335	4.371	4.500	2.875 SLIMLINE H-90	717
	AT675675.0	6.75/5.50	200.00	7.25/7.25	6/7	5.0	0.006	-0.009	-0.020	-0.031	-0.041	0.006	-0.009	-0.020	-0.031	-0.041	0.013	194.00	188.00	0.288	4.316	4.000	2.875 API REG	608
	AT675676.0	6.75/5.50	250.00	8.00/8.00	6/7	6.0	-0.009	-0.020	-0.020	-0.031	-0.041	-0.009	-0.020	-0.020	-0.031	-0.041	0.013	242.00	236.00	0.288	4.316	4.000	2.875 API REG	759
	AT675782.1 ESX	6.75/5.31	230.00	9.00/9.00	7/8	2.1	-0.007	-0.023	-0.033	-	-	-0.007	-0.023	-0.033	-	-	0.013	221.00	213.00	0.224	4.265	4.000	2.875 API REG	743
	AT675782.9 HTS	6.75/5.50	220.00	8.00/8.00	7/8	2.9	-0.002	-0.015	-0.025	-0.035	-	-0.002	-0.015	-0.025	-0.035	-	0.013	213.50	206.50	0.244	4.296	4.000	2.875 API REG	700
	AT675783.0	6.75/5.50	125.00	8.00/8.00	7/8	3.0	0.019	0.004	-0.008	-0.017	-	0.019	0.004	-0.008	-0.017	-	0.011	118.50	111.50	0.256	4.520	4.000	2.875 API REG	435
	AT675783.0 SLOW	6.75/5.50	204.00	7.50/7.50	7/8	3.0	0.006	-0.006	-0.014	-0.026	-	0.006	-0.006	-0.014	-0.026	-	0.011	197.50	191.00	0.255	4.570	4.000	2.875 API REG	685
	AT675783.3 HTS	6.75/5.50	245.00	8.00/8.00	7/8	3.3	0.000	-0.011	-0.021	-0.031	-	0.000	-0.011	-0.021	-0.031	-	0.012	238.50	231.50	0.255	4.500	4.000	2.875 API REG	877
	AT675785.0	6.75/5.50	194.50	8.00/8.00	7/8	5.0	0.019	0.004	-0.008	-0.017	-0.028	0.019	0.004	-0.008	-0.017	-0.028	0.011	188.00	181.00	0.256	4.520	4.000	2.875 API REG	694
	AT675785.7 SX	6.75/5.50	260.00	8.00/8.00	7/8	5.7	0.005	-0.005	-0.023	-0.035	-	0.005	-0.005	-0.023	-0.035	-	0.012	252.00	245.00	0.246	4.644	4.500	2.875 API REG	1002
	AT675786.0	6.75/5.50	235.00	8.00/8.00	7/8	6.0	0.019	0.004	-0.008	-0.017	-0.028	0.019	0.004	-0.008	-0.017	-0.028	0.011	223.00	216.00	0.256	4.520	4.500	2.875 API REG	831
	AT675786.4 (0)	6.75/5.50	245.00	8.00/8.00	7/8	6.4	0.019	0.004	-0.008	-0.017	-	0.019	0.004	-0.008	-0.017	-	0.011	238.50	231.50	0.256	4.520	4.000	2.875 API REG	883
AT6759102.1	6.75/5.50	81.00	8.00/8.00	9/10	2.1	0.012	-	-0.011	-	-	0.012	-	-0.011	-	-	0.013	75.00	68.00	0.194	4.312	4.300	2.875 API IF	261	
AT6759108.0	6.75/5.50	260.00	8.00/8.00	9/10	8.0	0.009	-0.003	-	-	-	0.009	-0.003	-	-	-	0.013	252.00	245.00	0.224	4.830	4.625	2.875 API REG	1016	
7"	AT700568.3 (0)	7.00/5.75	260.00	10.00/10.00	5/6	8.3	0.009	-0.006	-0.021	-0.034	-	0.009	-0.006	-0.021	-0.034	-	0.013	252.00	244.00	0.294	4.663	4.700	1.375-6 SA	833
	AT700568.6 (0)	7.00/5.75	275.00	10.00/10.00	5/6	8.6	0.015	-0.002	-0.015	-0.024	-	0.015	-0.002	-0.015	-0.024	-	0.013	267.00	254.50	0.324	4.703	4.380	1.375-6 SA	910
	AT7006711.4	7.00/5.75	275.00	10.00/10.00	6/7	11.4	0.000	-0.014	-0.027	-	-	0.000	-0.014	-0.027	-	-	0.013	267.00	259.00	0.306	4.689	4.500	2.875 SLIMLINE H-90	896
	AT700676.5 (0)	7.00/5.75	275.00	8.00/8.00	6/7	6.5	0.005	-0.008	-0.021	-0.033	-	0.005	-0.008	-0.021	-0.033	-	0.013	267.00	259.00	0.302	4.747	4.750	2.875 SLIMLINE H-90	932
	AT700678.4 (0)	7.00/5.75	275.00	8.00/8.00	6/7	8.4	0.005	-0.008	-0.020	-0.033	-0.045	0.005	-0.008	-0.020	-0.033	-0.045	0.013	267.00	259.00	0.302	4.747	4.750	2.875 SLIMLINE H-90	932
	AT700785.8 HT	7.00/5.75	300.00	10.00/10.00	7/8	5.8	0.004	-	-	-	-	0.004	-	-	-	-	0.011	292.00	284.00		4.800	4.750	1.375-6 SA	1225
	AT700786.8	7.00/5.75	246.00	11.00/11.00	7/8	6.8	0.002	-0.010	-0.021	-	-	0.002	-0.010	-0.021	-	-	0.011	233.00	226.00	0.250	4.538	4.500	2.875 SLIMLINE H-90	877
	AT700787.5	7.00/5.75	246.00	9.25/9.25	7/8	7.5	0.009	-	-	-	-	0.009	-	-	-	-	0.013	241.00	234.00	0.258	4.606	4.000	2.875 API REG	889
AT700788.5 (0)	7.00/5.75	300.00	7.00/7.00	7/8	8.5	0.007	-0.004	-	-	-	0.007	-0.004	-	-	-	0.013	294.00	288.00	0.268	5.024	5.000	1.375-6 SA	1269	
7 3/4"	AT775455.3	7.75/6.25	228.00	8.00/8.00	4/5	5.3	0.003	-0.010	-0.022	-0.035	-	0.003	-0.010	-0.022	-0.035	-	0.012	221.00	213.00	0.415	4.940	4.750	3.50 API IF	856
	AT775782.2	7.75/6.25	228.00	8.00/8.00	7/8	2.2	0.003	-	-	-	-	0.003	-	-	-	-	0.013	221.00	213.00	0.278	5.075	4.750	3.50 API IF	1043
	AT775782.5 SLOW	7.75/6.25	254.00	8.00/8.00	7/8	2.5	0.011	-0.003	-0.018	-0.034	-0.048	0.011	-0.003	-0.018	-0.034	-0.048	0.013	246.00	239.00	0.300	5.141	4.630	3.50 API REG	1157
	AT775784.0	7.75/6.25	203.25	8.00/8.00	7/8	4.0	0.013	-0.002	-0.017	-0.032	-	0.013	-0.002	-0.017	-0.032	-	0.013	196.25	188.25	0.293	5.186	4.750	3.50 API REG	956
8"	AT800455.3	8.00/6.25	228.00	8.00/8.00	4/5	5.3	0.003	-0.010	-0.022	-0.035	-	0.003	-0.010	-0.022	-0.035	-	0.012	221.00	213.00	0.415	4.940	4.750	3.50 API IF	856
	AT800674.0	8.00/6.25	206.00	8.00/8.00	6/7	4.0	0.006	-	-0.029	-	-	0.006	-	-0.029	-	-	0.012	199.00	192.00	0.336	4.958	4.750	3.50 API IF	809
	AT800675.0	8.00/6.25	250.00	9.00/9.00	6/7	5.0	0.006	-	-	-	-	0.006	-	-	-	-	0.012	244.00	237.00	0.336	4.958	4.750	3.50 API IF	995
	AT800676.0	8.00/6.25	300.00	8.00/8.00	6/7	6.0	0.006	-	-	-	-	0.006	-	-	-	-	0.012	293.00	286.00	0.336	4.958	4.750	3.50 API IF	1196
	AT800782.2	8.00/6.25	228.00	8.00/8.00	7/8	2.2	0.003	-	-	-	-	0.003	-	-	-	-	0.013	221.00	213.00	0.278	5.075	4.750	3.50 API IF	1043
	AT800782.5 SLOW	8.00/6.25	254.00	8.00/8.00	7/8	2.5	0.011	-0.003	-0.018	-0.034	-0.048	0.011	-0.003	-0.018	-0.034	-0.048	0.013	246.00	239.00	0.300	5.141	4.630	3.50 API REG	1157

Size	Model	STATOR															ROTOR							
		CONFIGURATION					FIT @ 75° F (Inch)										Minor Diameter Tolerance +/-	CONFIGURATION						
		Tube OD/ID Inch	Length Inch	Cutback Inch	Lobes	Stages	NBR-HPW					NBR - HPO						Overall Length Inch	Contour Length Inch	Ecc Inch	Major Diameter Inch	Head Diameter Inch	Thread Connection	Weight lb
							STD	.50S	10S	1.50S	20S	STD	.50S	10S	1.50S	20S								
8"	AT800783.0	8.00/6.25	160.00	8.00/8.00	7/8	3.0	0.017	-	-	-	-	0.017	-	-	-	-	0.013	153.00	145.00	0.293	5.186	4.750	3.50 API REG	745
	AT800783.4 ESX	8.00/6.25	300.00	8.00/8.00	7/8	3.4	0.002	-0.011	-0.026	-0.041	-	0.002	-0.011	-0.026	-0.041	-	0.013	293.00	285.00	0.291	5.307	4.750	3.50 API IF	1377
	AT800784.0	8.00/6.25	203.25	8.00/8.00	7/8	4.0	0.013	-0.002	-0.017	-0.032	-	0.013	-0.002	-0.017	-0.032	-	0.013	196.25	188.25	0.293	5.186	4.750	3.50 API REG	956
	AT800785.9 (O)	8.00/6.25	300.00	8.00/15.50	7/8	5.9	0.013	-0.002	-0.017	-	-	0.013	-0.002	-0.017	-	-	0.013	284.50	276.50	0.293	5.186	4.750	3.50 API REG	1388
	AT800896.0	8.00/6.50	206.00	8.00/8.00	8/9	6.0	0.010	-	-	-	-	0.010	-	-	-	-	0.013	192.00	185.00	0.273	5.459	4.750	3.50 API IF	1039
9 5/8"	AT962565.0	9.63/7.88	232.00	10.00/10.00	5/6	5.0	-0.005	-	-0.030	-	-	-0.005	-	-0.030	-	-	0.019	222.00	213.00	0.472	6.296	5.500	4.00 API FH	1410
	AT962675.0	9.63/7.88	218.00	8.00/8.00	6/7	5.0	0.011	-0.009	-0.028	-	-	0.011	-0.009	-0.028	-	-	0.019	202.00	195.00	0.428	6.403	5.500	4.00 API FH	1378
	AT962676.0	9.63/7.88	250.00	9.00/9.00	6/7	6.0	0.011	-	-	-	-	0.011	-	-	-	-	0.019	240.00	233.00	0.428	6.403	5.500	4.00 API FH	1642
	AT962783.9	9.63/7.88	300.00	10.00/10.00	7/8	3.9	0.003	-	-	-	-	0.003	-	-	-	-	0.019	290.00	281.00	0.368	6.515	5.500	4.00 API FH	1905
	AT962785.7	9.63/7.88	240.00	10.00/10.00	7/8	5.7	0.005	-	-	-	-	0.005	-	-	-	-	0.019	230.88	222.00	0.354	6.373	5.500	4.00 API FH	1651
11 1/4"	AT1125564.6	11.25/9.25	230.00	10.50/10.50	5/6	4.6	0.011	-	-	-	-	0.011	-	-	-	-	0.019	219.50	210.50	0.538	7.498	6.500	2.125-6 SA	1876
	AT1125565.0	11.25/7.88	232.00	10.00/10.00	5/6	5.0	-0.005	-	-0.030	-	-	-0.005	-	-0.030	-	-	0.019	222.00	213.00	0.472	6.296	5.500	4.00 API FH	1410
	AT1125675.0	11.25/7.88	218.00	8.00/8.00	6/7	5.0	0.011	-	-0.028	-	-	0.011	-	-0.028	-	-	0.019	202.00	195.00	0.428	6.403	5.500	4.00 API FH	1378
	AT1125675.5	11.25/9.25	250.00	10.50/10.50	6/7	5.5	0.018	-	-	-	-	0.018	-	-	-	-	0.020	240.00	230.00	0.487	7.683	6.500	2.125-6 SA	2260
	AT1125785.7	11.25/7.88	240.00	10.00/10.00	7/8	5.7	0.005	-	-	-	-	0.005	-	-	-	-	0.019	230.88	222.00	0.354	6.373	5.500	4.00 API FH	1651



POWER SECTION SPECIFICATION SUMMARY - METRIC

9/29/2020

Size	Model	CONFIGURATION							PERFORMANCE						MAXIMUM RECOMMENDED OPERATING CONDITIONS						COMPATIBILITY				
		Tube OD/ID mm		Stator Length mm		Lobes	Stages	Speed Rev/L	Torque Slope Nm/kPa	Max RPM	Pressure Diff kPa	Torque Nm	Power kW	Pressure Diff kPa	Torque Nm	Power kW	Weatherford	NOV	Dyna-Drill	PV	Roper				
		mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm										
4 3/4"	AT475456.0	121/95	4749.80	4/5	6.0	0.267	0.505	300	9720	4920	150	9720	4920	150	X	X	X	X	X						
	AT475456.3	121/95	5257.80	4/5	6.3	0.267	0.505	250	10270	5170	140	10270	5170	140	X	X	X	X							
	AT475459.7	121/99	5969.00	4/5	9.7	0.386	0.358	470	15720	5630	280	15720	5630	280											
	AT475568.3	121/95	6159.50	5/6	8.3	0.264	0.501	300	13510	6750	210	13510	6750	210		X	X		X						
	AT475782.0	121/95	4572.00	7/8	2.0	0.119	1.435	110	3240	4660	50	3240	4660	50	X		X	X							
	AT475782.2 SLOW	121/95	5029.20	7/8	2.2	0.082	1.555	80	3590	5550	50	3590	5550	50	X										
	AT475782.6 ESX	121/95	5822.95	7/8	2.6	0.069	1.856	80	4270	7820	70	4270	7820	70			X								
	AT475782.9	121/95	6350.00	7/8	2.9	0.081	1.579	80	4760	7430	60	4760	7430	60			X	X							
	AT475783.8	121/95	4749.80	7/8	3.8	0.143	0.908	140	6210	5600	80	6210	5600	80	X	X	X	X	X						
	AT475784.5 SX	121/95	5822.95	7/8	4.5	0.122	1.020	140	7310	7440	110	7310	7440	110			X								
	AT475785.0 RM	121/99	5029.20	7/8	5.0	0.164	0.781	190	8140	6330	130	8140	6330	130		X			X						
	AT475785.0 WF	121/99	5029.20	7/8	5.0	0.164	0.781	190	8140	6330	130	8140	6330	130	X				X						
AT475786.4	121/99	5969.00	7/8	6.4	0.166	0.747	190	10410	7760	150	10410	7760	150	X											
5"	AT500239.0	127/95	5080.00	2/3	9.0	0.835	0.172	1110	14620	2520	290	14620	2520	290											
	AT500456.0	127/95	4749.80	4/5	6.0	0.267	0.505	280	9720	4920	140	9720	4920	140	X	X	X	X	X						
	AT500456.3	127/95	5257.80	4/5	6.3	0.267	0.505	250	10270	5170	140	10270	5170	140	X	X	X	X	X						
	AT500459.7	127/99	5969.00	4/5	9.7	0.386	0.358	470	15720	5630	280	15720	5630	280											
	AT500563.7 Hi Flow	127/102	6350.00	5/6	3.7	0.092	1.418	120	6000	8500	110	6000	8500	110											
	AT500566.7	127/102	6350.00	5/6	6.7	0.166	0.791	220	10890	8580	200	10890	8580	200											
	AT500568.3	127/95	6159.50	5/6	8.3	0.264	0.501	300	13510	6750	210	13510	6750	210		X	X		X						
	AT5006710.0 (O)	127/102	6985.00	6/7	10.0	0.222	0.580	290	16200	9410	290	16200	9410	290											
	AT500676.0	127/102	4699.00	6/7	6.0	0.209	0.639	280	9720	6220	180	9720	6220	180		X		X							
	AT500678.0 (O)	127/102	6350.00	6/7	8.0	0.209	0.639	280	12960	8280	240	12960	8280	240	X	X	X	X							
	AT500678.8 (O)	127/102	6985.00	6/7	8.8	0.174	0.728	260	14270	10390	280	14270	10390	280				X							
	AT500679.0	127/102	6350.00	6/7	9.0	0.226	0.574	300	14620	8380	260	14620	8380	260											
	AT500782.0	127/95	4572.00	7/8	2.0	0.119	1.435	110	3240	4660	50	3240	4660	50	X		X	X							
	AT500782.2 SLOW	127/95	5029.20	7/8	2.2	0.082	1.555	80	3590	5550	50	3590	5550	50	X										



POWER SECTION SPECIFICATION SUMMARY - METRIC

9/29/2020

Size	Model	CONFIGURATION							PERFORMANCE						MAXIMUM RECOMMENDED OPERATING CONDITIONS						COMPATIBILITY				
		Tube OD/ID mm		Stator Length mm	Lobes	Stages	Speed Rev/L	Torque Slope Nm/kPa	Max RPM	Pressure Diff kPa	Torque Nm	Power kW	Pressure Diff kPa	Torque Nm	Power kW	Weatherford	NOV	Dyna-Drill	PV	Roper					
		mm	mm																						
5"	AT500782.6 ESX	127/95	5822.95	7/8	2.6	0.069	1.856	80	4270	7820	70	4270	7820	70			X								
	AT500782.9	127/95	6350.00	7/8	2.9	0.081	1.579	80	4760	7430	60	4760	7430	60			X	X							
	AT500783.0 ESX	127/102	6350.00	7/8	3.0	0.069	1.880	80	4900	9140	80	4900	9140	80			X								
	AT500783.7	127/99	5969.00	7/8	3.7	0.094	1.347	120	6000	8080	100	6000	8080	100	X										
	AT500783.8	127/95	4749.80	7/8	3.8	0.143	0.908	140	6210	5600	80	6210	5600	80	X	X	X	X	X						
	AT500784.5 SX	127/95	5822.95	7/8	4.5	0.122	1.020	140	7310	7440	110	7310	7440	110			X								
	AT500785.0 RM	127/99	5029.20	7/8	5.0	0.164	0.781	190	8140	6330	130	8140	6330	130		X			X						
	AT500785.0 WF	127/99	5029.20	7/8	5.0	0.164	0.781	190	8140	6330	130	8140	6330	130	X				X						
	AT500785.7	127/102	6350.00	7/8	5.7	0.136	0.932	150	9240	8610	140	9240	8610	140	X										
	AT500786.4	127/99	5969.00	7/8	6.4	0.166	0.747	190	10410	7760	150	10410	7760	150	X										
AT500788.2	127/102	6350.00	7/8	8.2	0.182	0.702	240	13310	9330	230	13310	9330	230			X									
AT500896.0	127/102	6350.00	8/9	6.0	0.135	0.964	140	9720	9370	140	9720	9370	140	X											
5.15"	AT5156710.9	131/102	6985.00	6/7	10.9	0.198	0.643	300	17720	11360	360	17720	11360	360											
	AT515788.3 HT (0)	131/102	6985.00	7/8	8.3	0.132	0.944	200	13510	12700	270	13510	12700	270											
5 1/4"	AT5256710.9	133/102	6985.00	6/7	10.9	0.198	0.643	300	17720	11360	360	17720	11360	360											
	AT525788.3 HT (0)	133/102	6985.00	7/8	8.3	0.132	0.944	200	13510	12700	270	13510	12700	270											
6 1/4"	AT625782.8	159/127	3302.00	7/8	2.8	0.087	1.481	130	4550	6720	90	4550	6720	90	X	X	X	X	X						
	AT625782.9 ESX	159/127	5810.25	7/8	2.9	0.043	3.018	80	4760	14200	120	4760	14200	120		X	X	X							
	AT625783.0 SLOW	159/127	5181.60	7/8	3.0	0.053	2.405	120	4900	11700	150	4900	11700	150	X		X								
	AT625783.3 ESX	159/127	6604.00	7/8	3.3	0.043	3.018	80	5380	16150	140	5380	16150	140	X		X								
	AT625784.8	159/127	5162.55	7/8	4.8	0.087	1.481	130	7790	11520	160	7790	11520	160	X	X	X	X	X						
6 1/2"	AT650457.0	165/140	5334.00	4/5	7.0	0.131	1.054	300	11380	11960	380	11380	11960	380	X	X	X	X	X						
	AT650565.4	165/135	5384.80	5/6	5.4	0.092	1.426	210	8760	12490	270	8760	12490	270	X										
	AT650568.2 (0)	165/140	6248.40	5/6	8.2	0.114	1.200	260	13310	15940	430	13310	15940	430			X								
	AT650675.0	165/140	5080.00	6/7	5.0	0.079	1.648	180	8140	13350	250	8140	13350	250	X	X	X	X	X						
	AT650676.0	165/140	6350.00	6/7	6.0	0.079	1.648	180	9720	16030	300	9720	16030	300				X							
	AT650782.1 ESX	165/135	5842.00	7/8	2.1	0.029	4.248	60	3450	14450	90	3450	14450	90	X		X								



POWER SECTION SPECIFICATION SUMMARY - METRIC

9/29/2020

Size	Model	CONFIGURATION							PERFORMANCE			MAXIMUM RECOMMENDED OPERATING CONDITIONS						COMPATIBILITY				
		Tube OD/ID mm	Stator Length mm	Lobes	Stages	Speed Rev/L	Torque Slope Nm/kPa	Max RPM	NBR-HPW			NBR-HPO			Weatherford	NOV	Dyna-Drill	PV	Roper			
									Pressure Diff kPa	Torque Nm	Power kW	Pressure Diff kPa	Torque Nm	Power kW								
6 1/2"	AT650782.8	165/127	3302.00	7/8	2.8	0.087	1.481	130	4550	6720	90	4550	6720	90	X	X	X	X	X			
	AT650782.9 ESX	165/127	5810.25	7/8	2.9	0.043	3.018	80	4760	14200	120	4760	14200	120		X	X	X				
	AT650782.9 HTS	165/140	5588.00	7/8	2.9	0.042	3.058	80	4760	14370	120	4760	14370	120		X	X					
	AT650783.0	165/140	3175.00	7/8	3.0	0.071	1.782	180	4900	8660	160	4900	8660	160	X	X	X	X	X			
	AT650783.0 (6.25) SLOW	165/127	5181.60	7/8	3.0	0.053	2.405	120	4900	11700	150	4900	11700	150	X		X					
	AT650783.0 SLOW	165/140	5181.60	7/8	3.0	0.042	3.097	100	4900	15060	160	4900	15060	160	X	X	X					
	AT650783.3 ESX	165/127	6604.00	7/8	3.3	0.043	3.018	80	5380	16150	140	5380	16150	140	X		X					
	AT650783.3 HTS	165/140	6223.00	7/8	3.3	0.040	3.333	90	5380	17830	170	5380	17830	170		X	X					
	AT650784.8	165/127	5168.90	7/8	4.8	0.087	1.481	130	7790	11520	160	7790	11520	160	X	X	X	X	X			
	AT650785.0	165/140	4940.30	7/8	5.0	0.071	1.782	180	8140	14440	270	8140	14440	270	X	X	X	X	X			
	AT650786.0	165/140	5969.00	7/8	6.0	0.071	1.781	180	9720	17330	330	9720	17330	330	X		X					
AT650786.4 (0)	165/140	6223.00	7/8	6.4	0.071	1.782	180	10410	18480	350	10410	18480	350	X								
6 3/4"	AT675457.0	171/140	5334.00	4/5	7.0	0.131	1.054	300	11380	11960	380	11380	11960	380	X	X	X	X	X			
	AT675565.4	171/135	5384.80	5/6	5.4	0.092	1.426	210	8760	12490	270	8760	12490	270	X							
	AT675568.2 (0)	171/140	6248.40	5/6	8.2	0.114	1.199	260	13310	15940	430	13310	15940	430		X	X					
	AT675675.0	171/140	5080.00	6/7	5.0	0.079	1.648	180	8140	13350	250	8140	13350	250	X	X	X	X	X			
	AT675676.0	171/140	6350.00	6/7	6.0	0.079	1.648	180	9720	16020	300	9720	16020	300				X				
	AT675782.1 ESX	171/135	5842.00	7/8	2.1	0.029	4.248	60	3450	14450	90	3450	14450	90	X		X					
	AT675782.9 HTS	171/140	5588.00	7/8	2.9	0.042	3.058	80	4760	14370	120	4760	14370	120		X	X	X				
	AT675783.0	171/140	3175.00	7/8	3.0	0.071	1.782	180	4900	8660	160	4900	8660	160	X	X	X	X	X			
	AT675783.0 SLOW	171/140	5181.60	7/8	3.0	0.042	3.097	100	4900	15060	160	4900	15060	160	X	X	X					
	AT675783.3 HTS	171/140	6223.00	7/8	3.3	0.040	3.333	90	5380	17830	170	5380	17830	170		X	X					
	AT675785.0	171/140	4940.30	7/8	5.0	0.071	1.781	180	8140	14440	270	8140	14440	270	X	X	X	X	X			
	AT675785.7 SX	171/140	6604.00	7/8	5.7	0.061	2.084	140	9240	19250	280	9240	19250	280		X	X	X				
	AT675786.0	171/140	5969.00	7/8	6.0	0.071	1.781	180	9720	17330	330	9720	17330	330	X		X					
	AT675786.4 (0)	171/140	6223.00	7/8	6.4	0.071	1.782	180	10410	18480	350	10410	18480	350	X							
AT6759102.1	171/140	2057.40	9/10	2.1	0.090	1.396	170	3450	4760	80	3450	4760	80									



POWER SECTION SPECIFICATION SUMMARY - METRIC

9/29/2020

Size	Model	CONFIGURATION							PERFORMANCE			MAXIMUM RECOMMENDED OPERATING CONDITIONS					COMPATIBILITY				
		Tube OD/ID mm		Stator Length mm	Lobes	Stages	Speed Rev/L	Torque Slope Nm/kPa	Max RPM	Pressure Diff kPa	Torque Nm	Power kW	Pressure Diff kPa	Torque Nm	Power kW	Weatherford	NOV	Dyna-Drill	PV	Roper	
		mm	mm																		
6 3/4"	AT6759108.0	171/140	6604.00	9/10	8.0	0.068	1.789	150	12960	23200	360	12960	23200	360	X						
7"	AT700568.3 (0)	178/146	6604.00	5/6	8.3	0.100	1.321	290	13440	17670	540	13440	17670	540							
	AT700568.6 (0)	178/146	6985.00	5/6	8.6	0.092	1.426	260	14000	19880	540	14000	19880	540							
	AT7006711.4	178/146	6985.00	6/7	11.4	0.111	1.207	290	13160	15850	480	13160	15850	480							
	AT700676.5 (0)	178/146	6985.00	6/7	6.5	0.061	2.147	170	10550	22630	400	10550	22630	400							
	AT700678.4 (0)	178/146	6985.00	6/7	8.4	0.079	1.657	230	13570	22440	540	13570	22440	540							
	AT700785.8 HT	178/146	7620.00	7/8	5.8	0.042	3.009	120	9450	28280	360	9450	28280	360							
	AT700786.8	178/146	6248.40	7/8	6.8	0.080	1.681	180	10970	18430	350	10970	18430	350			X				
	AT700787.5	178/146	6248.40	7/8	7.5	0.082	1.573	200	12200	19120	400	12200	19120	400		X					
AT700788.5 (0)	178/146	7620.00	7/8	8.5	0.069	1.934	200	13710	26490	550	13710	26490	550			X					
7 3/4"	AT775455.3	197/159	5791.20	4/5	5.3	0.063	2.149	220	8620	18470	430	8620	18470	430	X	X	X	X			
	AT775782.2	197/159	5791.20	7/8	2.2	0.024	5.823	70	3560	20650	150	3560	20650	150				X			
	AT775782.5 SLOW	197/159	6451.60	7/8	2.5	0.020	6.359	70	4070	25760	190	4070	25760	190	X						
	AT775784.0	197/159	5162.55	7/8	4.0	0.041	3.133	140	6440	20190	300	6440	20190	300	X	X	X	X	X		
8"	AT800455.3	203/159	5791.20	4/5	5.3	0.063	2.149	230	8620	18470	440	8620	18470	440	X	X	X	X			
	AT800674.0	203/159	5232.40	6/7	4.0	0.045	2.908	150	6440	18740	290	6440	18740	290				X			
	AT800675.0	203/159	6350.00	6/7	5.0	0.045	2.891	150	8140	23430	370	8140	23430	370		X		X	X		
	AT800676.0	203/159	7620.00	6/7	6.0	0.045	2.908	150	9670	28110	440	9670	28110	440		X		X	X		
	AT800782.2	203/159	5791.20	7/8	2.2	0.024	5.789	70	3590	20650	150	3590	20650	150				X			
	AT800782.5 SLOW	203/159	6451.60	7/8	2.5	0.020	6.397	70	4040	25760	190	4040	25760	190	X						
	AT800783.0	203/159	4064.00	7/8	3.0	0.042	3.105	140	4900	15100	220	4900	15100	220	X	X	X	X			
	AT800783.4 ESX	203/159	7620.00	7/8	3.4	0.023	5.576	80	5480	30550	260	5480	30550	260			X				
	AT800784.0	203/159	5162.55	7/8	4.0	0.041	3.119	140	6440	20110	290	6440	20110	290	X	X	X	X	X		
	AT800785.9 (0)	203/159	7620.00	7/8	5.9	0.041	3.119	140	9530	29650	430	9530	29650	430	X	X	X	X	X		
	AT800896.0	203/165	5232.40	8/9	6.0	0.057	2.199	170	9670	21260	380	9670	21260	380	X				X		
9 5/8"	AT962565.0	245/200	5892.80	5/6	5.0	0.034	4.088	170	8090	32930	590	8090	32930	590	X		X				
	AT962675.0	245/200	5537.20	6/7	5.0	0.034	4.015	170	8090	32350	580	8090	32350	580	X	X	X	X			





POWER SECTION SPECIFICATION SUMMARY - METRIC

9/29/2020

Size	Model	CONFIGURATION							MAXIMUM RECOMMENDED OPERATING CONDITIONS						COMPATIBILITY				
		PERFORMANCE				NBR-HPW			NBR-HPO			Weatherford	NOV	Dyna-Drill	PV	Roper			
		Tube OD/ID mm	Stator Length mm	Lobes	Stages	Speed Rev/L	Torque Slope Nm/kPa	Max RPM	Pressure Diff kPa	Torque Nm	Power kW						Pressure Diff kPa	Torque Nm	Power kW
9 5/8"	AT962676.0	245/200	6350.00	6/7	6.0	0.034	4.015	170	9670	38820	690	9670	38820	690	X	X	X	X	
	AT962783.9	245/200	7620.00	7/8	3.9	0.018	7.607	80	6310	47790	400	6310	47790	400			X		
	AT962785.7	245/200	6096.00	7/8	5.7	0.033	3.827	150	9190	35140	550	9190	35140	550	X	X			
11 1/4"	AT1125564.6	286/235	5842.00	5/6	4.6	0.024	6.248	160	7470	46300	780	7470	46300	780			X		
	AT1125565.0	286/200	5892.80	5/6	5.0	0.034	4.088	170	8090	32930	590	8090	32930	590	X		X		
	AT1125675.0	286/200	5537.20	6/7	5.0	0.034	4.015	170	8090	32350	580	8090	32350	580	X	X	X	X	
	AT1125675.5	286/235	6350.00	6/7	5.5	0.024	5.736	160	8910	50830	850	8910	50830	850		X	X		
	AT1125785.7	286/200	6096.00	7/8	5.7	0.033	3.827	150	9190	35140	550	9190	35140	550	X	X			